

GenieMat® DH765

ROLL-OUT SOUND CONTROL UNDERLAYMENT



PRODUCT SPECIFICATIONS

PRODUCT NAME:	GenieMat DH765
DESCRIPTION:	GenieMat DH is a floor underlayment mat made from up to 94% recycled content, optimized to achieve maximum impact sound reduction at minimum thickness. Ideal for new multifamily housing, retrofits, and commercial buildings.
APPLICATION:	Flat, resilient underlayment used directly under a variety of floor finishes such as vinyl, porcelain tile, and wood or placed directly under gypsum concrete in concrete, steel, and wood-frame construction.
FEATURES AND BENEFITS:	• Optimized design significantly reduces impact sound at minimum thickness • Mold, bacteria, fungi, and water resistant • Meets and exceeds pass criteria for point load test for crack isolation membrane (ANSI 118.12) • Can be installed directly under hard surface or resilient floor coverings • Meets requirements for VOC emissions (IAQ test, ASTM D5116/ISO 16000-9) • Complete floor covering system warranty available • Floorscore® certified • Third-party verified EPDs available • Qualifies for LEED® points
DIMENSION:	Roll: 4' wide, 13.5' long (nom. 1.22 m wide, nom. 4.11 m long)
THICKNESS:	7/16" (nom. 11 mm)
WEIGHT:	90 lb/Roll (40.8 kg/Roll)
AREA:	54 ft ² (5.02 m ²)
DENSITY:	Shall be > 44 lb/ft ³ (705 kg/m ³)
QUANTITY/PALLET:	20

GenieMat® DH765

ROLL-OUT SOUND CONTROL UNDERLAYMENT



TECHNICAL DATA

TYPE A HARDNESS (ASTM D2240):	45 (±5) Durometer
LABORATORY IMPACT INSULATION CLASS (ASTM E492/E2179, ISO 10140-3):	GenieMat DH765 tested over 8" (nom. 200 mm) concrete slab with 3/16" (nom. 4.8 mm) vinyl plank in a double floating installation, no ceiling, IIC 58 GenieMat DH765 tested over 8" (nom. 200 mm) concrete slab with 1/4" (nom. 6.4 mm) engineered hardwood in a glue down installation, no ceiling, IIC 57
NATURAL FREQUENCY:	Shall not be greater than 58 Hz at 200 psf (0.01 MPa) load
ROBINSON WHEEL TILE TEST (ASTM 627):	Light commercial with tile
POINT LOAD TEST FOR CRACK ISOLATION MEMBRANES (ANSI 118.12):	Exceeds pass criteria
DYNAMIC STIFFNESS (ASTM D5992, ISO 4664-1):	1832 lbf/in ³ (497 MN/m ³)
STATIC STIFFNESS (ASTM D5992, ISO 4664-1):	301 lbf/in ³ (82 MN/m ³)
DYNAMIC-STATIC STIFFNESS RATIO (ASTM D5992, ISO 4664-1):	6.09
VOC EMISSIONS (CDPH/EHLB STANDARD METHOD v1.2-2017):	FloorScore® certified
TEMPERATURE STABILITY:	-40°F to +240°F (-40°C to +115°C)

AROUND THE WORLD.

PLITEQ NORTH AMERICA

131 Royal Group Crescent
Vaughan, ON
L4H 1X9 Canada

4211, Yonge Street,
Suite 404, Toronto, ON M2P
2A9 Canada

2015 Main St,
Vancouver, BC
V5T 3C2 Canada

251 Little Falls Drive
Wilmington, DE
19808
United States of America
11701 N. 132nd Drive
Surprise, AZ
85379
United States of America

Calz. Gral. Mariano Escobedo
476-piso 12 Chapultepec
Morales, Anzures,
Miguel Hidalgo, 11590
Ciudad de México, CDMX
Mexico

T.+1 416 449 0049
T.+1 480 805 5560
T.+52 1 938 164 1551
info@pliteqacoustics.com
www.pliteqacoustics.com

PLITEQ UNITED KINGDOM

Office 205, Orega High
Holborn, 16 High Holborn,
London, WC1V 6BX
United Kingdom

T.+44 203 9846444
info@pliteqacoustics.com
www.pliteqacoustics.com/uk

PLITEQ MIDDLE EAST

European Business Centre
Dubai Investment Park
PO Box 473 512
United Arab Emirates

T. +971 4 567 4944
info@pliteqacoustics.com
www.pliteqacoustics.com/ae

PLITEQ ASIA PACIFIC

78 Shenton Way Tower 2,
6th Floor, Office Suite 25
079120, Singapore

T.+65 6813 2017
info@pliteqacoustics.com
www.pliteqacoustics.com/sg

PLITEQ AUSTRALIA

72 York Street, South
Melbourne, VIC, 3205
Australia

T.+61 3 9018 7696
info@pliteqacoustics.com
www.pliteqacoustics.com/au

