

GenieMat® FF70-9R

FLOATING FLOOR PANEL SYSTEM



PRODUCT SPECIFICATIONS

PRODUCT NAME:

GenieMat FF70-9R

DESCRIPTION:

Modular subfloor panels with discrete rubber isolators and mineral wool insulation, pre-assembled onto oriented strand board (OSB). **GenieMat FF70-9R** is used when superior sound control is required in mechanical rooms, sound studios, home theatres, entertainment venues, medical facilities, box-in-box constructions, fitness studios, gyms, or dance floors. **GenieMat FF70-9R** is used in commercial, industrial, and multifamily residential applications.

APPLICATION:

Shock absorbing and airborne/impact sound reducing subfloor panels to be used under cementitious toppings or dry laid boards (**GenieBoard®**, plywood, etc.).

FEATURES AND BENEFITS:

- Significantly improves impact and airborne sound ratings
- Increased load per isolator area yields superior natural frequency
- Eases fatigue, reduces joint and muscle stress, and prevents general discomfort and injuries associated with repetitive motion and high impact activities from athletic movements in yoga, pilates dance and basketball through force reduction as per DIN 18032
- No wet trades are required
- No shop drawings required
- Modular system designed for quick and easy assembly, eliminating the need for metal connector plates

DIMENSION:

Panel: 23-1/4" wide, 23-1/4" long (nom. 590 mm wide, nom. 590 mm long)

THICKNESS:

2-3/4" (nom. 70 mm)

PANEL WEIGHT:

11 lb (5 kg)

PANEL AREA:

3.75 ft² (0.35 m²)

QUANTITY/PALLET:

100

GenieMat® FF70-9R

FLOATING FLOOR PANEL SYSTEM



TECHNICAL DATA

LABORATORY IMPACT
INSULATION CLASS (ASTM
E492/E2179, ISO 10140-3):

Specified floor-ceiling assembly must be tested in a NVLAP-certified laboratory and comply with ASTM and ISO standards.

NATURAL FREQUENCY:

49 Hz at 50 psf (0.002 MPa) load
30 Hz at 200 psf (0.01 MPa) load
24 Hz at 400 psf (0.02 MPa) load
13 Hz at 2000 psf (0.1 MPa) load

DEFLECTION:


nom. 3/32 in (2.4 mm) at 400 psf (0.02 MPa) load

FIELD IMPACT INSULATION CLASS
(ASTM E1007, ISO 717-2, ISO 140-7):

Specified floor-ceiling assembly must meet requirement as stated by building code and/or acoustical consultant.

TEMPERATURE STABILITY:

-40°F to +240°F (-40°C to +115°C)



AROUND THE WORLD.

PLITEQ NORTH AMERICA

131 Royal Group Crescent
Vaughan, ON
L4H 1X9 Canada

4211, Yonge Street,
Suite 404, Toronto, ON M2P
2A9 Canada

2015 Main St,
Vancouver, BC
V5T 3C2 Canada

251 Little Falls Drive
Wilmington, DE
19808
United States of America
11701 N. 132nd Drive
Surprise, AZ
85379
United States of America

Calz. Gral. Mariano Escobedo
476-piso 12 Chapultepec
Morales, Anzures,
Miguel Hidalgo, 11590
Ciudad de México, CDMX
Mexico

T.+1 416 449 0049
T.+1 480 805 5560
T.+52 1 938 164 1551
info@pliteqacoustics.com
www.pliteqacoustics.com

PLITEQ UNITED KINGDOM

Office 205, Orega High
Holborn, 16 High Holborn,
London, WC1V 6BX
United Kingdom

T.+44 203 9846444
info@pliteqacoustics.com
www.pliteqacoustics.com/uk

PLITEQ MIDDLE EAST

European Business Centre
Dubai Investment Park
PO Box 473 512
United Arab Emirates

T. +971 4 567 4944
info@pliteqacoustics.com
www.pliteqacoustics.com/ae

PLITEQ ASIA PACIFIC

78 Shenton Way Tower 2,
6th Floor, Office Suite 25
079120, Singapore

T.+65 6813 2017
info@pliteqacoustics.com
www.pliteqacoustics.com/sg

PLITEQ AUSTRALIA

72 York Street, South
Melbourne, VIC, 3205
Australia

T.+61 3 9018 7696
info@pliteqacoustics.com
www.pliteqacoustics.com/au

