

Pliteq® FAS-B

WET SET ADHESIVE FOR SHIPLAP JOINTS AND GLUE ASSIST



PRODUCT SPECIFICATIONS

PRODUCT NAME:

Pliteq FAS-B

DESCRIPTION:

Pliteq FAS-B is a one-component, 100% solids, modified silane polymer-based adhesive. It is solvent-free, water-free, isocyanate-free, nonflammable, has low-odor, negligible VOC content, contains no hazardous chemicals as per OSHA Regulation CFR 1910.1200, and meets all federal, state, and local government indoor air quality regulations. This specifically formulated adhesive has an early grab that is fast curing and is easy to clean.

APPLICATION:

Pliteq FAS-B is ideal for wet-set glue down applications, engineered for improved adhesion of the **GenieBoard®** cementitious/high density structural cementitious/high density recycled subfloor panels. With its nozzle design, the application process is simplified. This adhesive is suitable for bonding the rebated edges of **GenieBoard** together. This adhesive can also be used to adhere Acrylic Infused Plank, Bamboo and Hardwood (engineered, parquet, solid). Approved substrates and surfaces for **Pliteq FAS-B** include, APA underlayment grade plywood and OSB; association grade particleboard; cement backer board; cementitious and anhydrite screeds; concrete and radiant heated subfloors that do not exceed 85°F (29°C); existing well-bonded non-cushion-backed vinyl; gypsum and lightweight concrete (primed with **Pliteq FAS-PS**); terrazzo (properly prepared with all waxes and surface finishes removed).

Pliteq® FAS-B

WET SET ADHESIVE FOR SHIPLAP JOINTS AND GLUE ASSIST



TECHNICAL DATA

BASE:	MS Polymer
APPEARANCE:	Off White
APPLICATION TEMPERATURE:	60-95°F (16-35°C)
APPLICATION RELATIVE HUMIDITY:	30-65%
RELATIVE HUMIDITY TEST (ASTM F2170):	N/A
SUBSTRATE MVER (ASTM F1869):	N/A
SUBSTRATE pH (ASTM F710):	N/A
SUBSTRATE POROSITY (ASTM F3191):	N/A
MOISTURE BARRIER:	No
FLASH TIME:	N/A
WORKING TIME:	45 minutes
CURE TIME:	12 hours
LIGHT TRAFFIC:	6 hours
HEAVY TRAFFIC:	6 hours
ROLLING LOADS:	N/A
CLEANING:	While wet: Use a damp cloth and water to remove. While soft: Use denatured alcohol, mineral spirits or an adhesive remover/stripper. Always check compatibility on a piece of scrap flooring.
STORAGE:	50-90°F (10-32°C)
SHELF LIFE:	1 year [Unopened container at 70°F (21°C)]
FREEZE/THAW STABILITY:	Protect from freezing; Stable to 10°F (-12°C) [3 cycles]
VOC CONTENT:	<0.1 g/L (<0.01 oz/gal)
CERTIFICATION:	Floor Score®; Green Label Plus®; GREENGUARD®; Material Health Certificate - Silver; mindful MATERIAL Library; Red List Free (LBC version 3.1); USGBC Member; LEED v4/4.1 Points
PACKAGING:	30 oz (887 mL) per Cartridge; 12 Cartridges per Case
QUANTITY/PALLET:	40 Cases

AROUND THE WORLD.

PLITEQ NORTH AMERICA

131 Royal Group Crescent
Vaughan, ON
L4H 1X9 Canada

4211, Yonge Street,
Suite 404, Toronto, ON M2P
2A9 Canada

2015 Main St,
Vancouver, BC
V5T 3C2 Canada

251 Little Falls Drive
Wilmington, DE
19808
United States of America
11701 N. 132nd Drive
Surprise, AZ
85379
United States of America

Calz. Gral. Mariano Escobedo
476-piso 12 Chapultepec
Morales, Anzures,
Miguel Hidalgo, 11590
Ciudad de México, CDMX
Mexico

T.+1 416 449 0049
T.+1 480 805 5560
T.+52 1 938 164 1551
info@pliteqacoustics.com
www.pliteqacoustics.com

PLITEQ UNITED KINGDOM

Office 205, Orega High
Holborn, 16 High Holborn,
London, WC1V 6BX
United Kingdom

T.+44 203 9846444
info@pliteqacoustics.com
www.pliteqacoustics.com/uk

PLITEQ MIDDLE EAST

European Business Centre
Dubai Investment Park
PO Box 473 512
United Arab Emirates

T. +971 4 567 4944
info@pliteqacoustics.com
www.pliteqacoustics.com/ae

PLITEQ ASIA PACIFIC

78 Shenton Way Tower 2,
6th Floor, Office Suite 25
079120, Singapore

T.+65 6813 2017
info@pliteqacoustics.com
www.pliteqacoustics.com/sg

PLITEQ AUSTRALIA

72 York Street, South
Melbourne, VIC, 3205
Australia

T.+61 3 9018 7696
info@pliteqacoustics.com
www.pliteqacoustics.com/au

