

PRODUCT SPECIFICATIONS

PRODUCT NAME:

Pliteq FAS-PS

DESCRIPTION:

Pliteq FAS-PS is a synthetic latex blend primer for improved adhesive bonds and as a primer for the **GenieMat® RST-PS** underlayments. It is acrylic latex based primer which is solvent and isocyanate free with extremely low odor and zero VOCs that contains no hazardous chemicals as per OSHA Regulation CFR 1910.1200, and meets all federal, state, and local government indoor air quality regulations.

APPLICATION:

Pliteq FAS-PS is engineered for improved adhesion of the **GenieMat RST-PS** peel and stick underlayments. With it's easy roll on application it is uniquely formulated to seal porous surfaces. Approved substrates and surfaces for **Pliteq FAS-PS** include, APA underlayment grade plywood and OSB; association grade particleboard; cement backer board; concrete and radiant heated subfloors that do not exceed 85°F (29°C); gypsum and lightweight concrete.

Pliteq® FAS-PS

SYNTHETIC LATEX BLEND PRIMER



TECHNICAL DATA

BASE:	Acrylic Latex
APPEARANCE:	Milky White
APPLICATION TEMPERATURE:	60-95°F (16-35°C)
APPLICATION RELATIVE HUMIDITY:	30-65%
RELATIVE HUMIDITY TEST (ASTM F2170):	75%
SUBSTRATE MVER (ASTM F1869):	5 lbs/1000 ft ² /24 hr (24.4 g/m ² / 24 hr)
SUBSTRATE pH (ASTM F710):	No testing required [5-14]
SUBSTRATE POROSITY (ASTM F3191):	CSP 1+, must pass [ASTM F3191]
MOISTURE BARRIER:	No
FLASH TIME:	N/A
WORKING TIME:	N/A
CURE TIME:	30-60 minutes
LIGHT TRAFFIC:	N/A
HEAVY TRAFFIC:	N/A
ROLLING LOADS:	N/A
CLEANING:	While wet: Use a dry cloth immediately to remove any excess primer from the surface. While soft: Use a remover/stripper, denatured alcohol or mineral spirits. Always check compatibility on a piece of scrap flooring.
STORAGE:	50-90°F (10-32°C)
SHELF LIFE:	2 years [Unopened container at 70°F (21°C)]
FREEZE/THAW STABILITY:	Protect from freezing; Stable to 50°F (10°C)
VOC CONTENT:	0 g/L (0 oz/gal)
CERTIFICATION:	Floor Score®; Green Label Plus®; GREENGUARD®; USGBC Member; LEED v4/4.1 Points
PACKAGING:	4 gallon (15.1 L)
QUANTITY/PALLET:	48 Pails

AROUND THE WORLD.

PLITEQ NORTH AMERICA

131 Royal Group Crescent
Vaughan, ON
L4H 1X9 Canada

4211, Yonge Street,
Suite 404, Toronto, ON M2P
2A9 Canada

2015 Main St,
Vancouver, BC
V5T 3C2 Canada

251 Little Falls Drive
Wilmington, DE
19808
United States of America
11701 N. 132nd Drive
Surprise, AZ
85379
United States of America

Calz. Gral. Mariano Escobedo
476-piso 12 Chapultepec
Morales, Anzures,
Miguel Hidalgo, 11590
Ciudad de México, CDMX
Mexico

T.+1 416 449 0049
T.+1 480 805 5560
T.+52 1 938 164 1551
info@pliteqacoustics.com
www.pliteqacoustics.com

PLITEQ UNITED KINGDOM

Office 205, Orega High
Holborn, 16 High Holborn,
London, WC1V 6BX
United Kingdom

T.+44 203 9846444
info@pliteqacoustics.com
www.pliteqacoustics.com/uk

PLITEQ MIDDLE EAST

European Business Centre
Dubai Investment Park
PO Box 473 512
United Arab Emirates

T. +971 4 567 4944
info@pliteqacoustics.com
www.pliteqacoustics.com/ae

PLITEQ ASIA PACIFIC

78 Shenton Way Tower 2,
6th Floor, Office Suite 25
079120, Singapore

T.+65 6813 2017
info@pliteqacoustics.com
www.pliteqacoustics.com/sg

PLITEQ AUSTRALIA

72 York Street, South
Melbourne, VIC, 3205
Australia

T.+61 3 9018 7696
info@pliteqacoustics.com
www.pliteqacoustics.com/au

