

GENIEMAT[®] FITO8

FITNESS FLOOR COVERINGS



PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat FITO8

DESCRIPTION: Resilient floor covering made from recycled rubber content and colored EPDM granules, used when superior impact shock, vibration, and noise control is required in fitness, gym, sports, and training facilities, and high-traffic or acoustically-sensitive environments.

APPLICATION: Used as a floor surface to cushion impacts from falling or dropping objects, ease fatigue, reduce joint and muscle stress, and prevent general discomfort and injuries associated with repetitive motion or standing for long periods of time.

COLOR: Available in a variety of colors and custom color blends

DIMENSION: Rollgood: 4' wide, 25' long (1.2 m wide, 7.6 m long)

THICKNESS: 5/16" (nom. 8 mm)

ROLL WEIGHT: 172 - 220 lb/roll (78.2 - 100 kg/roll)

ROLL AREA: 100 ft² (9.3 m²)

ROLLS/PALLET: 12

LEAD TIME: 2-3 weeks after receipt of order

ACCLIMATIZATION PERIOD: All product must acclimatize for at least 24 hours prior to installation at the same ambient conditions as the finished conditioned space.

TECHNICAL DATA

SHORE HARDNESS (D2240): >70 (+/- 5)

COMPRESSION SET (D395): -15 to -45% @25%

TABER ABRASION (C501): 0.45

For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2024.

®/™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com

GENIEMAT[®] FIT08

FITNESS FLOOR COVERINGS



TECHNICAL DATA CONTINUED

TENSILE STRENGTH (D412):	>300 psi
ELONGATION AT BREAK (D412):	>90%
COEFFICIENT OF FRICTION (D1894-95):	Wet 1.20 / Dry 1.20
DENSITY (D729):	>65 lb/ft ³
CRITICAL RADIANT FLUX (D395):	Class I/II*
FLAME SPREAD (E84):	135**
SMOKE DENSITY (E84):	<450**
TEAR (D624):	88.07 lbf/in (15.41 kN/m)
CHEMICAL RESISTANCE (F925-02):	No Change

*Class I available upon request.

** Same as carpet and wood.

CONTACT US

For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2024.

®/™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com