

GENIEMAT[®] FF25NC

ROLL-OUT FLOATING FLOORS



PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat FF25NC

DESCRIPTION: Robust rubber pad made up to 94% recycled rubber content used when superior sound control is required in mechanical rooms, sound studios, home theatres, entertainment venues, medical facilities, exercise, gym, and dance floors, and commercial, industrial, and multifamily housing.

APPLICATION: Shock absorbing and impact sound reducing pad to be used under gypsum, light-weight, full-weight concrete and other floating floor applications.

FEATURES AND BENEFITS:

- Significantly increases IIC and STC ratings
- Mold, bacteria, fungi, and water resistant
- Qualifies for LEED[®] points
- No potential mold-producing fibreglass
- Will not breakdown or move under load
- Easy to install, rolls out quickly, stays in place, and doesn't need to be adhered

DIMENSION: Rollgood: 4' wide, 15' long (1.22 m wide, 4.57 m long)

THICKNESS: 1" (nom. 25 mm)

ROLL WEIGHT: 210 lb/roll (95.3 kg/roll)

ROLL AREA: 60 ft² (5.57 m²)

ROLLS/PALLET: 6

LEAD TIME: 4-6 weeks after receipt of order

GENIEMAT[®] FF25NC

ROLL-OUT FLOATING FLOORS



TECHNICAL DATA

VOC EMISSIONS:
(CDPH/EHLB STANDARD
METHOD v1.2-2017) FloorScore compliant

TENSILE STRENGTH
(ASTM D412, DIE C): >35 psi

ELONGATION AT BREAK
(ASTM D412, DIE C): >60%

LABORATORY IMPACT
INSULATION CLASS
(ASTM E492): Specified floor-ceiling assembly must be tested in a NVLAP
certified laboratory and comply with ASTM standards.

TEMPERATURE STABILITY: -40°F to +240°F (-40°C to +115°C)



AROUND THE WORLD.

CONTACT US

PLITEQ NORTH AMERICA

131 Royal Group Crescent
Vaughan, ON
L4H 1X9 Canada

T. + 1 416 449 0049

info@pliteq.com
www.pliteq.com

PLITEQ UK

Irongate House
22-30 Dukes Place
London
EC3A 7LP

T. + 44 203 9846444

info@pliteq.co.uk
www.pliteq.co.uk

PLITEQ MIDDLE EAST

European Business Centre
Dubai Investment Park
PO Box 473 512
Dubai, UAE

T: +971 4 567 4944

info@pliteq.ae
www.pliteq.ae

PLITEQ ASIA PACIFIC

101 Cecil Street #19-13
Tong Eng Building Singapore
069533

T. +65 8452 6865

info@pliteq.sg
www.pliteq.sg



© Pliteq Inc.

®™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.