

# GENIEMAT® RST10 PRO

WATERPROOFING AND IMPACT SOUND CONTROL SYSTEM



## PRODUCT SPECIFICATION

PRODUCT NAME:	<b>GenieMat RST10 Pro</b>
DIMENSION:	Rollgood: 4' wide, 15' long (1.2 m wide, 4.6 m long)
THICKNESS:	3/8" (nom. 10 mm)
DENSITY:	Shall be > 1000 kg/m <sup>3</sup>
ROLLS/PALLET:	16

## TECHNICAL DATA

REDUCTION OF IMPACT SOUND PRESSURE LEVEL: (ASTM E492/E2179)	<b>GenieMat RST10 Pro</b> tested over 6" concrete slab with 12" x 12" ceramic tile, no ceiling, IIC 50, ΔIIC 21 dB
NATURAL FREQUENCY:	Shall not be greater than 68 Hz @ 400 psf loading
HIIC: (ASTM WK59631)	Shall be ≥ 63 when tested on an 8" concrete slab with vinyl Shall be ≥ 53 when tested on an 8" concrete slab with tile Shall be ≥ 61 when tested on an 8" concrete slab with engineered wood
POINT LOAD TEST FOR CRACK ISOLATION MEMBRANES: (ANSI 118.12)	Exceeds pass criteria
PUNCTURE TESTING WHEN INSTALLED UNDER LUXURY VINYL TILE: (ASTM F924)	No change when compared to puncture failure limit of luxury vinyl tile tested without underlayment
ROBINSON WHEEL TILE TEST: (ASTM C627)	Light commercial with tile
RESISTANCE TO IMPACT WHEN INSTALLED UNDER LUXURY VINYL TILE: (ASTM F1265)	Luxury vinyl tile shows no signs of breaking or cracking and meets standard criteria
ROLLING LOAD INDENTATION WHEN INSTALLED UNDER LUXURY VINYL TILE: (ASTM F2753)	Luxury vinyl tile shows no signs of indentation and plank separation for 12,500 cycles
WATER PROOFING (ANSI A118.10):	Meets and exceeds ANSI A118.10 Specification for Load Bearing, Bonded, Waterproof Membranes for Thin-set Ceramic Tile and Dimension Stone Installation per IPAL-0463-23

# GENIEMAT® RST10 PRO

WATERPROOFING AND IMPACT SOUND CONTROL SYSTEM



AVERAGE DYNAMIC  
STIFFNESS: (BS EN 29052) 407,416 lbf/ft<sup>3</sup> (64 MN/m<sup>3</sup>)

TYPE A HARDNESS:  
(ASTM D2240) 50 (± 5) durometer

VOC EMISSIONS:  
(CDPH/EHLB Standard  
Method v1.2-2017) FloorScore certified

LOAD/DEFLECTION FOR  
TILE FLOORS: Shall not have deflection greater than 2% of the thickness at loads up to 1000 psf (~48 kPa)

THERMAL RESISTANCE:  
(R-VALUE) 0.427 BTU/ hr · °F · ft<sup>2</sup> (0.075 W / m<sup>2</sup> · K)

THERMAL TRANSMITTANCE:  
(U-VALUE) 2.34 BTU/ hr · °F · ft<sup>2</sup> (13.33 W / m<sup>2</sup> · K)

WARRANTY: Shall have a 25 year warranty as an approved component of a full waterproofing floor system

TEMPERATURE STABILITY: -40°F to +240°F (-40°C to +115°C)





# AROUND THE WORLD.

## CONTACT US

### PLITEQ NORTH AMERICA

131 Royal Group Crescent  
Vaughan, ON  
L4H 1X9 Canada

T. + 1 416 449 0049

[info@pliteq.com](mailto:info@pliteq.com)  
[www.pliteq.com](http://www.pliteq.com)

### PLITEQ UK

Irongate House  
22-30 Dukes Place  
London  
EC3A 7LP

T. + 44 203 9846444

[info@pliteq.co.uk](mailto:info@pliteq.co.uk)  
[www.pliteq.co.uk](http://www.pliteq.co.uk)

### PLITEQ MIDDLE EAST

European Business Centre  
Dubai Investment Park  
PO Box 473 512  
Dubai, UAE

T: +971 4 567 4944

[info@pliteq.ae](mailto:info@pliteq.ae)  
[www.pliteq.ae](http://www.pliteq.ae)

### PLITEQ ASIA PACIFIC

101 Cecil Street #19-13  
Tong Eng Building Singapore  
069533

T. +65 8452 6865

[info@pliteq.sg](mailto:info@pliteq.sg)  
[www.pliteq.sg](http://www.pliteq.sg)

### PLITEQ AUSTRALIA & NEW ZEALAND

T. + 61 3 9018 7696  
T. + 61 476 757 736

[info@pliteq.com.au](mailto:info@pliteq.com.au)  
[www.pliteq.com.au](http://www.pliteq.com.au)



© PLITEQ INC.

\*™ TRADEMARKS OF PLITEQ INC. THE INFORMATION PROVIDED IS ACCURATE TO THE BEST OF OUR KNOWLEDGE AT THE TIME OF ISSUE. HOWEVER, WE RESERVE THE RIGHT TO MAKE CHANGES WHEN NECESSARY WITHOUT FURTHER NOTIFICATION. SUGGESTED APPLICATION MAY NEED TO BE MODIFIED TO CONFORM WITH LOCAL BUILDING CODES AND CONDITIONS. WE CANNOT ACCEPT RESPONSIBILITY FOR PRODUCTS THAT ARE NOT USED, OR INSTALLED, TO OUR SPECIFICATIONS. ALL LISTED DIMENSIONS ARE NOMINAL.