

PRODUCT SPECIFICATIONS

PRODUCT NAME:	GenieMat RSTo3PS
DESCRIPTION:	GenieMat RST is a flat, resilient, reduced sound transmission mat made from 94% recycled rubber content with a laminated pressure-sensitive adhesive, used directly under hard surface floor finishes and over concrete and wood construction.
APPLICATION:	It is used when superior sound control is required in multi-family housing, high-rises, or commercial buildings and protects ceramic tile, porcelain and stone from substrate cracks.
FEATURES AND BENEFITS:	<ul style="list-style-type: none">• Mold, bacteria, fungi, and water resistant• Exceeds pass criteria for point load test for crack isolation membrane (ANSI 118.12)• Meets requirements for VOC emissions (IAQ test, ASTM D5116)• Qualifies for LEED[®] points• Complete floor covering system warranty available• Floorscore[®] certified• Third-party verified EPDs available
DIMENSION:	Roll: 4' wide, 50' long (1.2 m wide, 15.2 m long)
THICKNESS:	1/8" (nom. 3 mm)
WEIGHT:	120 lb/Roll (54.4 kg/Roll)
AREA:	200 ft ² (18.58 m ²)
DENSITY:	Shall be > 62.43 lb/ft ³ (1000 kg/m ³)
QUANTITY/PALLET:	16

GenieMat[®] RSTo3PS

PEEL & STICK SOUND CONTROL UNDERLAYMENT



TECHNICAL DATA

TYPE A HARDNESS (ASTM D2240):	50 (±5) Durometer
REDUCTION OF IMPACT SOUND PRESSURE LEVEL (ASTM E492/E2179):	GenieMat RSTo3PS tested over 8" concrete slab with vinyl plank floor covering, no ceiling, shall have ≥ IIC 52 and ΔIIC 18dB as per ASTM E2179
NATURAL FREQUENCY:	Shall not be greater than 92 Hz at 400 psf (0.02 MPa) load
HIIC (ASTM E3222):	Shall be ≥ 58 when tested on an 8" (203.2 mm) concrete slab with vinyl Shall be ≥ 55 when tested on an 8" (203.2 mm) concrete slab with engineered wood Shall be ≥ 45 when tested on a 6" (152.4 mm) concrete slab with tile
POINT LOAD TEST FOR CRACK ISOLATION MEMBRANES (ANSI 118.12):	Exceeds pass criteria
PUNCTURE TESTING WHEN INSTALLED UNDER LUXURY VINYL TILE (ASTM F924):	No change when compared to puncture failure limit of luxury vinyl tile tested without underlayment
ROBINSON WHEEL TILE TEST (ASTM C627):	Extra heavy commercial with tile
RESISTANCE TO IMPACT WHEN INSTALLED UNDER LUXURY VINYL TILE (ASTM F1265):	Luxury vinyl tile shows no signs of breaking or cracking and meets standard criteria
ROLLING LOAD INDENTATION WHEN INSTALLED UNDER LUXURY VINYL TILE (ASTM F2753):	Luxury vinyl tile shows no signs of indentation and plank separation for 12,500 cycles
DYNAMIC STIFFNESS (ASTM D5992, D4473, D4065):	60544.5 lbf/in (10603 N/mm)
DYNAMIC-STATIC STIFFNESS RATIO (ASTM D5992, D4473, D4065):	124.59
VOC EMISSIONS (CDPH/EHLB STANDARD METHOD v1.2-2017):	FloorScore [®] certified

GenieMat[®] RSTo3PS

PEEL & STICK SOUND CONTROL UNDERLAYMENT



LOAD/DEFLECTION FOR TILE FLOORS:

Shall not have deflection greater than 2% of the thickness at loads up to 1,000 psf (~48 kPa)

THERMAL TRANSMITTANCE (U-VALUE):

7.81 BTU/ hr·°F·ft² (44.08 W/m²·K)

WARRANTY:

Shall have a 25 year warranty as an approved component of a full waterproofing floor system

TEMPERATURE STABILITY:

-40°F to +240°F (-40°C to +115°C)





AROUND THE WORLD.

PLITEQ INC.

131 Royal Group Crescent
Vaughan, ON
L4H 1X9 Canada

4211, Yonge Street,
Suite 404, Toronto, ON
M2P 2A9 Canada

2015 Main St,
Vancouver, BC
V5T 3C2 Canada

T.+1 416 449 0049
info@pliteq.com
www.pliteq.com

PLITEQ (DE)

251 Little Falls Drive
Wilmington, DE
19808
United States of America

PLITEQ (AZ)

11701 N. 132nd Drive
Surprise, AZ
85379
United States of America

T.+1 480 805 5560
info@pliteq.com
www.pliteq.com

PLITEQ (UK) LTD.

Office 205, Orega High
Holborn, 16 High Holborn,
London, WC1V 6BX
United Kingdom

T.+44 203 9846444
info@pliteq.co.uk
www.pliteq.co.uk

PLITEQ MEXICO

Calz. Gral. Mariano
Escobedo 476-piso 12
Chapultepec Morales,
Anzures,
Miguel Hidalgo, 11590
Ciudad de México, CDMX
Mexico

T.+52 1 938 164 1551

PLITEQ ASIA PACIFIC PTE LTD.

#19-13, 101 Cecil Street,
Tong Eng Building, 069533
Singapore

T.+65 6813 2017
info@pliteq.sg
www.pliteq.sg

PLITEQ BUILDING MATERIALS TRADING LLC.

European Business Centre
Dubai Investment Park
PO Box 473 512
United Arab Emirates

T. +971 4 567 4944
info@pliteq.ae
www.pliteq.ae

PLITEQ AUSTRALIA PTY LTD.

72 York Street, South
Melbourne, VIC, 3205
Australia

T.+61 3 9018 7696
info@pliteq.com.au
www.pliteq.com.au

