

# GENIEMAT<sup>®</sup> RST12

ROLL-OUT SOUND CONTROL UNDERLAYMENT



## PRODUCT SPECIFICATIONS

PRODUCT NAME:	<b>GenieMat RST12</b>
DESCRIPTION:	GenieMat RST is a flat, resilient, reduced sound transmission mat made from 94% recycled rubber content, used directly under hard surface floor finishes and over concrete and wood construction.
APPLICATION:	It is used when superior sound control is required in multi-family housing, high-rises, or commercial buildings and protects ceramic tile, porcelain and stone from substrate cracks.
FEATURES AND BENEFITS:	<ul style="list-style-type: none"><li>• Mold, bacteria, fungi, and water resistant</li><li>• Exceeds pass criteria for point load test for crack isolation membrane (ANSI 118.12)</li><li>• Meets requirements for VOC emissions (IAQ test, ASTM D5116)</li><li>• Qualifies for LEED<sup>®</sup> points</li><li>• Complete floor covering system warranty available</li><li>• Floorscore<sup>®</sup> certified</li></ul>
DIMENSION:	Roll: 4' wide, 12.5' long (1.2 m wide, 3.8 m long)
THICKNESS:	15/32" (nom. 12 mm)
WEIGHT:	120 lb/Roll (54.4 kg/Roll)
AREA:	50 ft <sup>2</sup> (4.65 m <sup>2</sup> )
DENSITY:	Shall be > 62.43 lb/ft <sup>3</sup> (1000 kg/m <sup>3</sup> )
QUANTITY/PALLET:	16

# GENIEMAT<sup>®</sup> RST12

ROLL-OUT SOUND CONTROL UNDERLAYMENT



## TECHNICAL DATA

TYPE A HARDNESS (ASTM D2240):	50 (+/-5) Durometer
REDUCTION OF IMPACT SOUND PRESSURE LEVEL: (E492/E2179)	<b>GenieMat RST12</b> tested over 8" concrete slab with 12" x 12" ceramic tile, no ceiling, IIC 55 dB
NATURAL FREQUENCY:	Shall not be greater than 61 Hz at 400 psf (0.02 MPa) load
HIIC: (WK59631)	Shall be $\geq$ 57 when tested on an 8" concrete slab with tile
POINT LOAD TEST FOR CRACK ISOLATION MEMBRANES: (ANSI 118.12)	Exceeds pass criteria
PUNCTURE TESTING WHEN INSTALLED UNDER LUXURY VINYL TILE: (F924)	No change when compared to puncture failure limit of luxury vinyl tile tested without underlayment
ROBINSON WHEEL TILE TEST: (C627)	Light commercial with tile
RESISTANCE TO IMPACT WHEN INSTALLED UNDER LUXURY VINYL TILE: (F1265)	Luxury vinyl tile shows no signs of breaking or cracking and meets standard criteria
ROLLING LOAD INDENTATION WHEN INSTALLED UNDER LUXURY VINYL TILE: (F2753)	Luxury vinyl tile shows no signs of indentation and plank separation for 12,500 cycles
AVERAGE DYNAMIC STIFFNESS: (BS EN 29052)	381,953 lbf/ft <sup>3</sup> (60 MN/m <sup>3</sup> )
VOC EMISSIONS (CDPH/EHLB STANDARD METHOD v1.2-2017):	FloorScore certified
LOAD/DEFLECTION FOR TILE FLOORS:	Shall not have deflection greater than 2% of the thickness at loads up to 1,000 psf (~48 kPa)
THERMAL TRANSMITTANCE: (U-VALUE)	1.95 BTU/ hr·°F·ft <sup>2</sup> (11.01 W/m <sup>2</sup> ·K)

# GENIEMAT<sup>®</sup> RST12

ROLL-OUT SOUND CONTROL UNDERLAYMENT



WARRANTY:

Shall have a 25 year warranty as an approved component of a full waterproofing floor system

TEMPERATURE STABILITY:

-40°F to +240°F (-40°C to +115°C)





# AROUND THE WORLD.

## CONTACT US

### PLITEQ NORTH AMERICA

131 Royal Group Crescent  
Vaughan, ON  
L4H 1X9 Canada

T. + 1 416 449 0049

[info@pliteq.com](mailto:info@pliteq.com)  
[www.pliteq.com](http://www.pliteq.com)

### PLITEQ UK

Irongate House  
22-30 Dukes Place  
London  
EC3A 7LP

T. + 44 203 9846444

[info@pliteq.co.uk](mailto:info@pliteq.co.uk)  
[www.pliteq.co.uk](http://www.pliteq.co.uk)

### PLITEQ MIDDLE EAST

European Business Centre  
Dubai Investment Park  
PO Box 473 512  
Dubai, UAE

T: +971 4 567 4944

[info@pliteq.ae](mailto:info@pliteq.ae)  
[www.pliteq.ae](http://www.pliteq.ae)

### PLITEQ ASIA PACIFIC

101 Cecil Street #19-13  
Tong Eng Building Singapore  
069533

T. +65 8452 6865

[info@pliteq.sg](mailto:info@pliteq.sg)  
[www.pliteq.sg](http://www.pliteq.sg)

### PLITEQ AUSTRALIA & NEW ZEALAND

72 York Street, South  
Melbourne, VIC, 3205

T. + 61 3 9018 7696  
T. + 61 476 757 736

[info@pliteq.com.au](mailto:info@pliteq.com.au)  
[www.pliteq.com.au](http://www.pliteq.com.au)

