

GENIE[®]MAT[®] FF50NC

ROLL-OUT FLOATING FLOORS



PATENTS: US 8,240,430 US 8,556,029 CA 2,500,956 CA 2,503,420

PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat FF50NC

DESCRIPTION: Robust rubber pad made from 92% recycled rubber content used when superior sound control is required in mechanical rooms, sound studios, home theatres, entertainment venues, medical facilities, exercise, gym, and dance floors, and commercial, industrial, and multifamily housing.

APPLICATION: Shock absorbing and impact sound reducing pad to be used under gypsum, light-weight or full-weight concrete.

FEATURES AND BENEFITS:

- Significantly increases IIC and STC ratings
- Mold, bacteria, fungi, and water resistant
- Qualifies for LEED[®] points
- No potential mold-producing fibreglass
- Will not break down or move under load
- Easy to install, rolls out quickly, stays in place, and doesn't need to be adhered

DIMENSION: Rollgood: 4' wide, 15' long (0.1 m wide, 0.4 m long)

THICKNESS: 2" (51 mm)

ROLL WEIGHT: 200 lb/roll (90.7 kg/roll)

ROLL AREA: 30 ft² (2.8 m²)

ROLLS/PALLET: 12 (2 x GenieMat FF25NC)

LEAD TIME: 2-3 weeks after receipt of order

For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2020.

[®] Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com

GENIEMAT[®] FF50NC

ROLL-OUT FLOATING FLOORS



PATENTS: US 8,240,430 US 8,556,029 CA 2,500,956 CA 2,503,420

TECHNICAL DATA

SHEET WEIGHT: 6.6 lb/ft² (32.2 kg/m²)

**TENSILE STRENGTH
(ASTM D412, DIE C):** 35 psi minimum

**ELONGATION AT BREAK
(ASTM D412, DIE C):** 60% minimum

**TYPE A HARDNESS
(ASTM D2240):** 30 durometer

**LABORATORY IMPACT
INSULATION CLASS
(ASTM E492):** Specified floor-ceiling assembly must be tested in a NVLAP-certified laboratory and comply with ASTM standards.

**FIELD IMPACT INSULATION
CLASS (ASTM E1007):** Specified floor-ceiling assembly must meet requirement as stated by building code and/or acoustical consultant.

TEMPERATURE STABILITY: -40°F to +240°F (-40°C to +115°C)

CONTACT US

For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2020.

[®] Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com